

Material Safety Data Sheet

acc. to OSHA and ANSI

Printing date 11/10/2008

Reviewed on 10/03/2008

1 Identification of substance:

Product details:

Product name: 2-Methyl-3-buten-2-ol

Stock number:

B20790

L08070

Manufacturer/Supplier:

Alfa Aesar, A Johnson Matthey Company

Johnson Matthey Catalog Company, Inc.

30 Bond Street

Ward Hill, MA 01835-8099

Emergency Phone: (978) 521-6300

CHEMTREC: (800) 424-9300

Web Site: www.alfa.com

Information Department: Health, Safety and Environmental Department

Emergency information:

During normal hours the Health, Safety and Environmental Department.

After normal hours call Chemtrec at (800) 424-9300.

2 Composition/Data on components:

Chemical characterization:

Description: (CAS#)

2-Methyl-3-buten-2-ol (CAS# 115-18-4): 100%

Identification number(s):

EINECS Number: 204-068-4

3 Hazards identification

Hazard description:



Xn Harmful

F Highly flammable

Information pertaining to particular dangers for man and environment

R 11 Highly flammable.

R 22 Harmful if swallowed.

R 36/37 Irritating to eyes and respiratory system.

Classification system

HMIS ratings (scale 0-4)

(Hazardous Materials Identification System)

HEALTH	1
FIRE	3
REACTIVITY	1

Health (acute effects) = 1

Flammability = 3

Reactivity = 1

4 First aid measures

After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm.

Seek immediate medical advice.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 2)

Material Safety Data Sheet

acc. to OSHA and ANSI

Printing date 11/10/2008

Reviewed on 10/03/2008

Product name: 2-Methyl-3-buten-2-ol

(Contd. of page 1)

Seek immediate medical advice.

After eye contact

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing Seek immediate medical advice.

5 Fire fighting measures

Suitable extinguishing agents

Carbon dioxide, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Special hazards caused by the material, its products of combustion or resulting gases:

In case of fire, the following can be released:

Carbon monoxide and carbon dioxide

Protective equipment:

Wear self-contained respirator.

Wear fully protective impervious suit.

6 Accidental release measures

Person-related safety precautions:

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

Measures for environmental protection:

Do not allow material to be released to the environment without proper governmental permits.

Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Keep away from ignition sources.

Additional information:

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Handling**Information for safe handling:**

Keep container tightly sealed.

Ensure good ventilation at the workplace.

Information about protection against explosions and fires:

Keep ignition sources away.

Protect against electrostatic charges.

Fumes can combine with air to form an explosive mixture.

Storage**Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Information about storage in one common storage facility:

Store away from oxidizing agents.

(Contd. on page 3)

Material Safety Data Sheet

acc. to OSHA and ANSI

Printing date 11/10/2008

Reviewed on 10/03/2008

Product name: 2-Methyl-3-buten-2-ol

(Contd. of page 2)

Protect from heat.

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed containers.

8 Exposure controls and personal protection**Additional information about design of technical systems:**

Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute.

Components with limit values that require monitoring at the workplace:

Not required.

Additional information: No data**Personal protective equipment****General protective and hygienic measures**

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Breathing equipment:

Use suitable respirator when high concentrations are present.

Protection of hands:

Impervious gloves

Check protective gloves prior to each use for their proper condition.

Material of gloves

The selection of suitable gloves not only depends on the material, but also on quality. Quality will vary from manufacturer to manufacturer.

Eye protection: Safety glasses**Body protection:** Protective work clothing.**9 Physical and chemical properties:****General Information**

Form:	Liquid
Color:	Colorless
Odor:	Like alcohol

Change in condition

Melting point/Melting range:	-28°C (-18°F)
Boiling point/Boiling range:	98-99°C (208-210°F)
Sublimation temperature / start:	Not determined

Flash point:	13°C (55°F)
---------------------	-------------

Ignition temperature:	380°C (716°F)
------------------------------	---------------

Decomposition temperature:	Not determined
-----------------------------------	----------------

Explosion limits:

Lower:	1.5 Vol %
Upper:	9.4 Vol %

(Contd. on page 4)

-USA-

Material Safety Data Sheet

acc. to OSHA and ANSI

Printing date 11/10/2008

Reviewed on 10/03/2008

Product name: 2-Methyl-3-buten-2-ol

(Contd. of page 3)

Vapor pressure:	Not determined
Density at 20°C (68°F):	0.82 g/cm ³
Solubility in / Miscibility with Water:	Fully miscible
Viscosity: dynamic at 20°C (68°F):	2.6 mPas

10 Stability and reactivity

Thermal decomposition / conditions to be avoided:

Decomposition will not occur if used and stored according to specifications.

Materials to be avoided:

Oxidizing agents

Heat

Dangerous reactions No dangerous reactions known

Dangerous products of decomposition: Carbon monoxide and carbon dioxide

11 Toxicological information

Acute toxicity:

Irritation of skin No irritation (rabbit) (External MSDS)

Irritation of eyes Irritation (rabbit) (External MSDS)

LD/LC50 values that are relevant for classification:

Oral	LD50	1074 mg/kg (rat)
Inhalative	LC50	2300 mg/m ³ (mouse)
	LC50/4H	>21200 mg/m ³ /4H (rat)

Primary irritant effect:

on the skin: May cause mild irritation

on the eye: Irritating effect.

Sensitization: No sensitizing effects known.

Subacute to chronic toxicity:

Subacute to chronic toxicity:

The Registry of Toxic Effects of Chemical Substances (RTECS) reports the following effects in laboratory animals:

Brain and Coverings - other degenerative changes.

Blood - changes in cell count (unspecified).

Blood - changes in serum composition (e.g. TP, bilirubin, cholesterol).

Kidney, Ureter, Bladder - other changes in urine composition.

Immunological including Allergic - decreased immune response.

Liver - other changes.

Additional toxicological information:

To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.

No classification data on carcinogenic properties of this material is available from the EPA, IARC, NTP, OSHA or ACGIH.

USA

(Contd. on page 5)

Material Safety Data Sheet

acc. to OSHA and ANSI

Printing date 11/10/2008

Reviewed on 10/03/2008

Product name: 2-Methyl-3-buten-2-ol

(Contd. of page 4)

12 Ecological information:

General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Do not allow material to be released to the environment without proper governmental permits.

13 Disposal considerations

Product:

Recommendation

Consult state, local or national regulations to ensure proper disposal.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

14 Transport information

DOT regulations:



Hazard class: 3
Identification number: UN1987
Packing group: II
Proper shipping name (technical name): ALCOHOLS, N.O.S. (2-Methyl-3-buten-2-ol)
Label: 3

Land transport ADR/RID (cross-border)



ADR/RID class: 3 (F1) Flammable liquids
Danger code (Kemler): 33
UN-Number: 1987
Packaging group: II
Description of goods: 1987 ALCOHOLS, N.O.S. (2-Methyl-3-buten-2-ol)

Maritime transport IMDG:



IMDG Class: 3
UN Number: 1987
Label: 3
Packaging group: II

(Contd. on page 6)

Material Safety Data Sheet

acc. to OSHA and ANSI

Printing date 11/10/2008

Reviewed on 10/03/2008

Product name: 2-Methyl-3-buten-2-ol

(Contd. of page 5)

Proper shipping name: ALCOHOLS, N.O.S. (2-Methyl-3-buten-2-ol)**Air transport ICAO-TI and IATA-DGR:**

ICAO/IATA Class:	3
UN/ID Number:	1987
Label	3
Packaging group:	II
Proper shipping name:	ALCOHOLS, N.O.S. (2-Methyl-3-buten-2-ol)

15 Regulations**Product related hazard informations:****Hazard symbols:**

Xn Harmful

F Highly flammable

Risk phrases:

11 Highly flammable.

22 Harmful if swallowed.

36/37 Irritating to eyes and respiratory system.

Safety phrases:

16 Keep away from sources of ignition - No smoking.

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

37 Wear suitable gloves.

National regulations

All components of this product are listed in the U.S. Environmental Protection Agency Toxic Substances Control Act Chemical substance Inventory.

All components of this product are listed on the Canadian Domestic Substances List (DSL).

Information about limitation of use:

For use only by technically qualified individuals.

16 Other information:

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Material Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Department issuing MSDS: Health, Safety and Environmental Department.**Contact:** Paul V. Connolly