

Safety Data Sheet
according to 1907/2006/EC, Article 31

Revision: 01.12.2009

Printing date 01.12.2009

1 Identification of substance**Product details**

Trade name

4-Methyl-2-pentanone

Stock number:

A11618
L12842

Manufacturer/Supplier:

Alfa Aesar
Shore Road
Port of Heysham Industrial Park
Heysham Lancashire LA3 2XY
United Kingdom

Office Tel: +44 (0) 1524 850506

Informing department:

Product safety department.

Emergency information:

Call Carechem 24 at +44 (0) 1865 407333

2 Hazards identification

Hazard designation:

Xn Harmful
F Highly flammable

Information pertaining to particular dangers for man and environment

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.
 R 11 Highly flammable.
 R 20 Harmful by inhalation.
 R 36/37 Irritating to eyes and respiratory system.
 R 66 Repeated exposure may cause skin dryness or cracking.

GHS label elements

**Danger**

H225 - Highly flammable liquid and vapour.

**Warning**

H332 - Harmful if inhaled.
 H319+EUH066 - Causes serious eye irritation. Repeated exposure may cause skin dryness or cracking.
 H335 - May cause respiratory irritation.
 P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P243 Take precautionary measures against static discharge.
 P312 Call a POISON CENTER or doctor/physician if you feel unwell.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Prevention:

Response:

Storage:

Disposal:

3 Composition/information on ingredients

Chemical characterization:

4-Methyl-2-pentanone (CAS# 108-10-1)

Designation: (CAS#)

Identification number(s):

203-550-1

EINECS Number:

606-004-00-4

Index number:

4 First aid measures

After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

After skin contact

Seek immediate medical advice.
Instantly wash with water and soap and rinse thoroughly.

After eye contact

Seek immediate medical advice.

After swallowing

Rinse opened eye for several minutes under running water. Then consult doctor.
Seek immediate medical advice.**5 Fire fighting measures**

Suitable extinguishing agents

CO2, sand, extinguishing powder. Do not use water.

For safety reasons unsuitable extinguishing agents

Water.

Special hazards caused by the material, its products of combustion or flue gases:

Can be released in case of fire:
Carbon monoxide and carbon dioxide

Protective equipment:

Wear self-contained breathing apparatus.
Wear full protective suit.**6 Accidental release measures**

Person-related safety precautions:

Wear protective equipment. Keep unprotected persons away.

Measures for environmental protection:

Ensure adequate ventilation
Keep away from ignition sources

Measures for cleaning/collecting:

Do not allow material to be released to the environment without proper governmental permits.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to item 13.

Additional information:

Ensure adequate ventilation.
 Keep away from ignition sources.
 See Section 7 for information on safe handling
 See section 8 for information on personal protection equipment.
 See Section 13 for information on disposal.

7 Handling and storage

Handling

Information for safe handling:

Keep containers tightly sealed.
 Store in cool, dry place in tightly closed containers.
 Ensure good ventilation/exhaustion at the workplace.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Fumes can combine with air to form an explosive mixture.

Storage

Requirements to be met by storerooms and containers:

Store in cool location.

Information about storage in one common storage facility:

Store away from oxidizing agents.

(Contd. on page 2)

GB

Trade name 4-Methyl-2-pentanone

(Contd. of page 1)

Further information about storage conditions:

Keep container tightly sealed.
Store in cool, dry conditions in well sealed containers.

8 Exposure controls and personal protection**Additional information about design of technical systems:**

Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute.

Components with critical values that require monitoring at the workplace:

Methyl isobutyl ketone (4-Methyl-2-pentanone)
ppm

ACGIH TLV 50
Austria MAK 100
Denmark TWA 25 (skin)
France VME 50
Japan OEL 50 (skin)
Netherlands MAC-TGG 25; 50-MAC-K
Norway TWA 25
Poland TWA 200 mg/m³; 300 mg/m³-STEL
Sweden NGV 25; 50-KTV
OSHA PEL 100
No data

Additional information:**Personal protective equipment****General protective and hygienic measures**

The usual precautionary measures should be adhered to in handling the chemicals.
Keep away from foodstuffs, beverages and food.
Instantly remove any soiled and impregnated garments.
Wash hands during breaks and at the end of the work.
Avoid contact with the eyes.

Breathing equipment:**Protection of hands:****Material of gloves**

Avoid contact with the eyes and skin.
Use breathing protection with high concentrations.
Check protective gloves prior to each use for their proper condition.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Eye protection:

Safety glasses

Body protection:

Face protection
Protective work clothing.

9 Physical and chemical properties:**General Information**

Form: Liquid
Colour: Colourless
Smell: Like ketone

Change in condition

Melting point/Melting range: -83°C
Boiling point/Boiling range: 117-118°C
Sublimation temperature / start: Not determined

Flash point: 13°C

Ignition temperature: 460°C

Decomposition temperature: Not determined

Critical values for explosion:

Lower: 1.2 Vol %
Upper: 8 Vol %

Steam pressure at 20°C: 20 hPa

Density at 20°C 0.8 g/cm³

Solubility in / Miscibility with

Water at 20°C: 19 g/l

10 Stability and reactivity**Thermal decomposition / conditions to be avoided:**

No decomposition if used and stored according to specifications.

Materials to be avoided:

Oxidizing agents

Dangerous reactions:

No dangerous reactions known

Dangerous products of decomposition:

Carbon monoxide and carbon dioxide

11 Toxicological information**Acute toxicity:****LD/LC50 values that are relevant for classification:**

Oral	LD50	1900 mg/kg (mouse) 2080 mg/kg (rat)
	LD50	>3 gm/kg (rabbit)
Inhalative	LC50/4H	8200-16400 mg/m ³ /4H (rat)
Irritation of skin	mild	500 mg/24H (rabbit)

Primary irritant effect:**on the skin:**

May cause irritation

on the eye:

Irritant effect.

Sensitization:

No sensitizing effect known.

Additional toxicological information:

To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.
No classification data on carcinogenic properties of this material is available from the EPA, IARC, NTP, OSHA or ACGIH.

12 Ecological information:**General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water.
Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.
Do not allow material to be released to the environment without proper governmental permits.

Safety Data Sheet
according to 1907/2006/EC, Article 31

Revision: 01.12.2009

Printing date 01.12.2009

Trade name **4-Methyl-2-pentanone**

(Contd. of page 2)

13 Disposal considerations

Product:
Recommendation Consult state, local or national regulations for proper disposal.
Hand over to disposers of hazardous waste.
Must be specially treated under adherence to official regulations.

Uncleaned packagings:
Recommendation: Disposal must be made according to official regulations.

14 Transport information**Land transport ADR/RID and GGVS/GGVE (cross-border/domestic)**

ADR/RID-GGVS/E Class: 3 (F1) Flammable liquids.
Kemler Number: 33
UN-Number: 1245
Packaging group: II
Label: 3
Designation of goods: 1245 METHYL ISOBUTYL KETONE
Limited quantities (LQ) LQ4
Transport category 2
Tunnel restriction code D/E

Maritime transport IMDG/GGVSea:

IMDG/GGVSea Class: 3
UN Number: 1245
Label: 3
Packaging group: II
EMS Number: F-E, S-D
Marine pollutant: No
Correct technical name: METHYL ISOBUTYL KETONE

Air transport ICAO-TI and IATA-DGR:

ICAO/IATA Class: 3
UN/ID Number: 1245
Label: 3
Packaging group: II
Correct technical name: METHYL ISOBUTYL KETONE

UN "Model Regulation":
UN1245, METHYL ISOBUTYL KETONE, 3, II

15 Regulatory information**Designation according to EC guidelines:****Code letter and hazard designation of product:**

Xn Harmful
F Highly flammable

Risk phrases:
11 Highly flammable.
20 Harmful by inhalation.
36/37 Irritating to eyes and respiratory system.
66 Repeated exposure may cause skin dryness or cracking.

Safety phrases:
9 Keep container in a well-ventilated place.
16 Keep away from sources of ignition - No smoking.
29 Do not empty into drains.

National regulations

Information about limitation of use: Employment restrictions concerning young persons must be observed.
For use only by technically qualified individuals.

Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

16 Other information:

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Material Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Department issuing data specification sheet: Health, Safety and Environmental Department.

Contact: Zachariah Holt

Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent